

Product Information Sheet



Water Cut off

PIN # 1101

Item Description

Cartridge : 10 fl oz (300 ml)

Carton: 25 cartridges

Carton Weight: Approximately 27 lbs (12 kg)

product Number

CH-300100

Product Information

Water cut off is designed to provide a seal when used in compression as required

Method of Application:

1. Surface where the water cut off is applied shall be free of loose debris, foreign materials and other contaminants
2. Apply a 3/8" (9.5 mm) to 1/2" (12.7 mm) bead to the substrate surface
3. Bring the mating surface of the flashing membrane into contact with the water cut off sealant
4. Roll or press the membrane firmly against the water cut off and substrate, avoid wrinkles
5. Complete as per proSeal guideline details

Storage:

- Store in original unopened containers, at temperatures between 60 & 80° F (15° & 26° C)
- When exposed to lower temperatures, restore to room temperature prior to use
- For best results, rotate stock to ensure material does not exceed a one (1) year shelf life

Shelf Life:

- Shelf life of one (1) year can be expected when stored in original sealed containers at specified temperatures
- Shelf life can be shortened if exposed to sustained elevated temperatures

Coverage Rates:

- Coverage of approximately 10' (3.1m) per cartridge of 3/8" to 1/2" (9.5 to 12.7mm) bead

Clean Up:

Recommended cleaners are mineral spirits, naphtha, or kerosene

Precautions:

1. Review material data safety sheet prior to use
2. Flammable. Keep away from open flames during storage and use. Do not smoke when using
3. Do not thin
4. Do not contaminate with foreign materials
5. Avoid prolonged contact on skin
6. Use only in well ventilated areas
7. This product is not designed to be used as an exposed sealant

For further information contact
RPW Associates, Inc
905-875-1108 / -866-202-6900