

# Product Information Sheet



## EPDM Self adhering pipe flashing

**PIN # 1102**

### Item Description

1"-6" moulded EPDM

1"-3" moulded EPDM

Carton: 10 per case

Carton Weight: 10 lbs ( 4.5 kg)

Base: Rubber Polymer

### Product Number

CH-300105

CH-300108

### Product Information

#### Description:

proSeal EPDM pipe boots are specifically designed to be used in roofing applications for flashings round penetrations on EPDM roof membranes. The proSeal EPDM pipe boot fit various penetrations and must be cut to correct diameter size before installation

#### Application:

- 1- Ensure the surface of the EPDM is clean using proSeal tape prime or splice wash
- 2- Ensure the surface is allowed to fully dry
- 3- Cut along the top edge of the ring in accordance to the correct pipe diameter
- 4- Remove the release paper and apply over the pipe penetration
- 5- Firmly press the flange onto the roof membrane
- 6- Roll the surface edges to ensure full and proper adhesion

#### Storage:

- Store in original unopened containers indoors at temperature between 60°F (15.6°C) & 80°F(26.7°C)
- Do not store on roof in direct sunlight or temperatures over 100°F ( 37.7°C)
- When exposed to lower temperatures, restore to room temperature prior to use
- Shelf life of one (1) year can be expected when stored properly
- Shelf life can shorted if exposed to elevated temperatures

#### Precautions:

- Do not install on uneven surfaces or substrates
- Refer to MSDS safety data sheets

#### Compliance:

Post-Consumer recycled content: 0%

Pre consumer recycled content: 0%

#### Fit Guidelines

1"	25 mm
1.5"	38 mm
2"	50 mm
3"	75 mm
4"	100 mm
5"	125 mm
6"	150 mm

For further information contact  
**RPW Associates, Inc**  
**905-875-1108 / -866-202-63900**