

Product Information Sheet



PVC / TPO Self adhering pipe flashing PIN # 1103

Item Description

1"-6" moulded thermoplastic polyolefin

1"-3" moulded thermoplastic polyolefin

Carton: 10 per case

Carton Weight: 10 lbs (4.5 kg)

Base: Rubber Polymer

Product Number

PT-400308

PT-400306

Product Information

Description:

proSeal PVC / TPO pipe boots are specifically designed to be used in roofing applications for flashings round penetrations on PVC / TPO roof membranes. The proSeal PVC / TPO pipe boot fit various penetrations and must be cut to correct diameter size before installation

Application:

- 1- Ensure the surface of the PVC / TPO is clean using proSeal tape prime or splice wash
- 2- Ensure the surface is allowed to fully dry
- 3- Cut along the top edge of the ring in accordance to the correct pipe diameter
- 4- Remove the release paper and apply over the pipe penetration
- 5- Firmly press the flange onto the roof membrane
- 6- Roll the surface edges to ensure full and proper adhesion

Storage:

- Store in original unopened containers indoors at temperature between 60°F (15.6°C) & 80°F(26.7°C)
- Do not store on roof in direct sunlight or temperatures over 100°F (37.7°C)
- When exposed to lower temperatures, restore to room temperature prior to use
- Shelf life of one (1) year can be expected when stored properly
- Shelf life can shorted if exposed to elevated temperatures

Precautions:

- Do not install on uneven surfaces or substrates
- Refer to MSDS safety data sheets

Compliance:

Post-Consumer recycled content: 0%

Pre consumer recycled content: 0%

Fit Guidelines

1"	25 mm
1.5"	38 mm
2"	50 mm
3"	75 mm
4"	100 mm
5"	125 mm
6"	150 mm

For further information contact

RPW Associates, Inc

905-875-1108 / -866-202-63900