

Product Information Sheet



proStrip in-seam tapes

PIN # 1104

Item Description

ProStrip InSeam Tapes are a butyl sealer used for bonding various roofing membranes together in typical seam applications in the roofing industry

product Number

CH-300116 Black 3" x 100'	4/ctn
CH-300117 Black 6" x 100'	2/ctn
CH-300207 White 3" x 100'	4/ctn
CT-300208 White 6" x 100'	2/ctn

Product Information

Thickness: +/- 35 mil
Density (lb/gal): 9.19
Flashpoint (TCC): >240 C
Odor: Slight
Volatile, % by Volume: <99.9%
Penetration (ASTM D 217): 100/130 mm
Adhesion: To most clean, dry substrates/surfaces



Method of Application:

1. Overlap membrane based on conditions or specifications clean both sides of membrane in the seam
2. Always clean and prime membrane using proSeal tape primers
3. Allow primer to dry before installing tapes.
4. Chalk lines are recommended for aligning tape. Allow release paper to stick out ½" from the membrane overlap.
5. Install tape into seam leaving release paper on the tape.
6. Remove release paper on bottom of in-seam tapes & roll using metal seam roller with some force perpendicular to the tape product. This helps avoid fish mouths.
7. Start in the middle of the seam and work towards the ends.
8. Fold top membrane piece into the release paper and THEN pull release paper off, use your hand to guide membrane carefully on to tape before final rolling with metal roller.

Storage:

Store in warehouse without excessive heat (below 130°F (50°C). Do NOT store long term on roof. Excessive heat will promote curing even while in the box.

Shelf Life:

Indefinite, actual weather exposure & accelerated testing indicates that hardening, shrinking, cracking, drying or loss of adhesion will not occur

Coverage Rates:

- Coverage of approximately 10' (3.1m) per cartridge of 3/8" to ½" (9.5 to 12.7mm) bead

Precautions:

Effected by: petroleum, grease, oil, solvents, vegetable or mineral oil, animal fats

For further information contact
RPW Associates, Inc
905-875-1108 / -866-202-63900