

Product Information Sheet



proSeal Cover Tapes

PIN # 1109

Item Description

Roll Size Net weight per roll Packaging

9" x 70' feet 31.5 lbs (14.3 kg) 1 roll per carton
12" x 70 feet 42 lbs (19 kg) 1 roll per carton,
18" X 70' feet 63 lbs (28.6 KG)1 roll per carton
9" x 70' feet 31.5 lbs (14.3 kg) 1 roll per carton
12" x 70 feet 42 lbs (19 kg) 1 roll per carton,
18" X 70' feet 63 lbs (28.6 KG)1 roll per carton

product Number

CH-300096 - white
CH-300097 - white
CH-300098 - white
CH-300123 - black
CH-300121 - black
CH-300122 - black

Product Information

The proSeal's Cover Tape are specifically developed for use with single-ply membrane roofing systems such as EPDM, TPO & PVC. The proSeal Cover Tapes is used in conjunction with the proSeal Tape Primer to strip gravel stops, drip aprons, seams or batten bars, and can be used to make repairs to cut membranes.

Method of Application:

- membrane surface where the Cover Tape are applied must be cleaned and primed.
- Cover Tape will not adhere to dusted/dirty surfaces.
- Remove any dirt or dust by wiping with a clean rag.
- Install Cover Tape immediately after primer flashes off to minimize potential dust contamination and promote adhesion in colder weather.
- Position the Cover Tape over the area to be covered and press down the exposed tape portion using firm, even hand pressure across the entire area. Continue this process until the full area to be flashed is completed.
- Immediately roll the Cover Tape with a 2" (50 mm) wide roller, using positive pressure. Roll across the flashing edge, not parallel
- Cover Tape is used to flash many different roofing system structures and penetrations. The specific method of applying the flashing for each individual situation is different. The appropriate detail should be consulted prior to application.

Storage:

- Prolonged jobsite storage temperatures in excess of 90°F (32°C) will shorten product shelf life.
- In warm, sunny weather, keep Cover Tape rolls in original box in a shaded area until ready to use.
- Storage and use of Cover Tape at temperatures below 40°F (4°C) will result in a loss of tape tack and, in extreme cases, will result in no bond to the substrate. Overnight storage must be available to keep the temperature of the Cover Tape at a minimum of 60°F (15°C).
- Jobsite storage must be provided to maintain a minimum tape temperature of 40°F (4°C).
- Cover Tape must be stored in a dry area.

For further information contact
RPW Associates, Inc
905-875-1108 / 866-202-6900

Product Information Sheet



BENEFITS & SUPPLEMENTAL STATEMENTS

- Contains no solvent
- Ease of installation
- Labor savings up to 50%
- Reduces application problems of adhesives
- Superior tack and green strength
- Strength improves with age
- Superior peel and shear strengths

Shelf Life:

- Shelf life is 1 year when properly stored between 60°F and 80°F. Stock should be rotated.

Warranty:

- When installed in accordance to the *proSeal* specifications and in acceptable workmanship the *proSeal cover tapes* are acceptable for use in conjunction with the *proSeal* 10 year modular warranty program

PROTECTION & SAFETY

proSeal maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

PRECAUTIONS

- Avoid prolonged contact with skin. In case of contact with skin, thoroughly wash affected area with soap and water.
- Due to solvent flash-off, condensation may occur on freshly applied primer when the ambient temperature is near the dew point. If condensation develops, the application of primer must be discontinued as proper adhesion will not be achieved.
- Allow the primer surface to dry and apply a thin freshener coat of primer to the previously coated surface and apply Cured Cover Tape when conditions allow.
- Cured Cover Tape is cured and cannot be use for flashing corners, pipes or T-Joint Covers.
- Do not allow waste products (petroleum, grease, oil, solvents, vegetable or mineral oil, animal fats, etc.) or direct steam venting to come in contact with the Cover Tape.
- KEEP OUT OF REACH OF CHILDREN

For further information contact
RPW Associates, Inc
905-875-1108 / 866-202-6900