

Product Information Sheet



LVOC Tape primers

PIN # 1112

Item Description

1 gal containers wt: 8 lbs
4 per case wt: 32 lbs

product Number

CH-300119

Product Information

Description

proSeal LVOC Primer is used in the preparation of the membrane surface on TPO & EPDM single ply membrane for the application of in-seam tapes, cover tapes and flashing membrane LVOC primers. VOC content does not exceed 250 grams / ltr and is acceptable for restricted air quality managed districts. Local and state regulations should be verified.

Method of Application:

1. Mix thoroughly before & during use. Contents should appear uniform
2. Surface must be clean and free of dirt, dust and debris, clean with brooms and rags as required
3. Apply LVOC primers with a scotch pad a back & forth manner to the areas required. Surface should appear uniform in colour with no puddles or streaks, ensure full contact is made when applying
4. Allow surface to fully dry and confirm, Dry time can vary due to ambient temperatures

Storage:

Keep material out of direct sunlight until ready to use

Shelf Life:

Typical shelf life is one (1) year when stored at temperatures between 60° F & 80°F (16°C & 27°C)

Coverage Rates:

- Coverage of approximately 10' (3.1m) per cartridge of 3/8" to 1/2" (9.5 to 12.7mm) bead

Precautions:

- **WARNING flammable, do not use near open flame, or other possible ignition do not smoke**
- Do not use near or child
- Use neoprene or nitrile gloves as well as eye protection
- Use only in well ventilated areas
- Do not thin
- Do not apply with rags, rollers or brushes

For further information contact
RPW Associates, Inc
905-875-1108 / 866-202-6900